

C-Fiber

Femtosecond Fiber Laser 1560 nm




Menlo Systems' fiber-based femtosecond laser sources integrate the latest achievements in fiber technology into easy-to-use products. Menlo Systems' unique figure 9[®] design results in reproducible and long-term stable operation. It is based on the well-established Nonlinear Amplifying Loop Mirror (NALM) mode locking mechanism. Both oscillator and amplifier use polarization maintaining (PM) fiber components only, ensuring excellent stability and low-noise operation. The laser is maintenance free, user installed and ready to use at the press of a single button. Customize your laser with the available options to match the requirements of your application. Complete synchronization solution is available with laser and synchronization electronics. All components from one supplier with full automation guarantees hands off operation and more time for your experiments.

PERFORMANCE DATA


Amplitude noise

< 0.5% rms (over 24h)



Reproducibility

Identical and consistent laser performance



MenloSystems

KEY SPECIFICATIONS

- Wavelength 1560 nm
- Output Power >500 mW
- Pulse Length <90 fs
- Repetition Rate 50-250 MHz

APPLICATIONS

- Synchronization and Timing
- Ultrafast Spectroscopy
- Supercontinuum Generation
- Material Characterization
- Testing at Telecom Wavelengths

FEATURES

- High Stability
- Low Amplitude and Phase Noise
- All-PM Solution
- Single Mode-Lock State
- Menlo figure 9[®] Technology

OPTIONS

- **SYNC100**
Repetition Rate Synchronization
Tunable cavity length by high-bandwidth piezo-controlled synchronization
- **RRE-SYNCR0**
Repetition Rate Stabilization
Feedback electronics to phase lock pulses to an external clock (see separate data sheet for more details)
- **VARIO**
User-Defined Repetition Rate
Factory-set value selectable in the 50-250 MHz range
- **MULTIBRANCH**
Additional Seed Ports
Seeding of multiple amplifiers with optional subsequent frequency conversion to cover multiple wavelengths

